



A Step Ahead...

# QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219  
QUAKERTOWN, PENNSYLVANIA 18951-0219  
(215) 536-3520 FAX (215) 536-6464  
[www.quakercolor.com](http://www.quakercolor.com)

## Technical Data Sheet- Leather Finishing Products

Product Code: AB-1014

### DESCRIPTION

AB-1014 is a high solids, soft yet tough, acrylic polymer with very low Tg

### APPLICATIONS

Used in embossable base coats for automotive leathers

### FEATURES

- Soft low tack very dry to the touch
- Excellent embossing print retention
- Excellent high temperature no cut embossing properties
- Good compatibility with polyurethane resins
- APEO Free

### PROPERTIES

Percent Solids, weight	35%
Specific Gravity, 25°C	1.03g/cm <sup>3</sup>
pH, typical value	8.5
Viscosity, cPs	20

### STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.