



A Step Ahead...

QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

Technical Data Sheet- Leather Finishing Products

Product Code: AR-1263

DESCRIPTION

AR-1263 is a high performance tough acrylic polymer with low Tg

APPLICATIONS

Used alone or in combination with polyurethane resins in base or topcoat applications for automotive leathers

FEATURES

- Soft, tough, low tack, dry to the touch
- Excellent water resistance
- Excellent hydrolytic flex properties
- Good compatibility with polyurethane resins
- Excellent Bally Flex properties
- APEO Free

PROPERTIES

Percent Solids, weight	36%
Specific Gravity, 25°C	1.04g/cm ³
pH, typical value	7.3
Viscosity, cPs	22

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.