



A Step Ahead...

QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

Technical Data Sheet- Leather Finishing Products

Product Code: JK-535F

DESCRIPTION

JK-535F is a medium hard, NMP free, high performance aliphatic polyester polyurethane dispersion.

APPLICATIONS

- Topcoat and intermediate coat for leather applications where good embossing properties, abrasion resistance, and flexibility properties are required.

FEATURES

- Good water resistance
- Tough flexible films
- Excellent embossing properties
- Good taber abrasion resistance

PROPERTIES

Percent Solids, weight	38
Specific Gravity, 25°C	1.04
pH, typical value	8.2
Viscosity, cPs	100

STORAGE

Store in a cool, dry place, preferably less than 80°F to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.