



QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead...

Technical Data Sheet

Product Code: PR-1326

DESCRIPTION

PR-1326 is a medium-soft, NMP free, high performance aliphatic polyether polyurethane dispersion. It is a blending component used to adjust properties to meet performance requirements.

APPLICATIONS

- Blending with polyurethane dispersions
- Blending with waterborne acrylic polymers

FEATURES

- Economical blending resin
- Increased flexibility
- Adhesion to flexible substrates

PROPERTIES

Appearance	Clear Light Amber Liquid
Percent Solids, weight	32 – 38
Specific Gravity, 25°C	1.04
Viscosity, cps	1000
pH, typical value	8.0
Tensile Strength, psi	2000
Modulus (100%), psi	300
Elongation, %	1100

STORAGE

Not intended for long term storage.
Must be maintained between 50 to 90 degrees Fahrenheit.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.