



A Step Ahead...

QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

Technical Data Sheet

Product Code: PR-1576

DESCRIPTION

PR-1576 is a very-soft, NMP free, high performance aliphatic polyurethane dispersion. It is a blending component used to adjust properties to meet performance requirements.

APPLICATIONS

- Adhesion promoter and increased flexibility

FEATURES

- Exceptional adhesion to a variety of substrates
- Low use levels

PROPERTIES

Appearance	White Liquid
Percent Solids, weight	30 – 34
Specific Gravity, 25°C	1.03
Viscosity, cps	100
pH, typical value	7.7

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.