QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead…

Technical Data Sheet- Leather Finishing Products

Product Code: AB-1517

DESCRIPTION

AB-1517 is a compact low cost embossable base coat binder for automotive leather.

APPLICATIONS

Used in roll or spray applications to produce automotive leathers with exceptional coverage, softness, and aesthetic break properties. Can be crosslinked with 2% XL-1219 Carbodiimide to enhance/maximize properties.

FEATURES

- No cut embossing with good grain retention
- Excellent bally flex and cold crack properties
- Excellent hydrolytic and Xenon exposure flexibility resistance
- Exceptional softness and aesthetic break appearance
- Low cost

PROPERTIES

Percent Solids, weight	29
Specific Gravity, 25°C	1.04 g/cm3
pH, typical value	8.7
Viscosity, cPs	600

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.