QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead…

Technical Data Sheet- Leather Finishing Products

Product Code: AP-1662 Aqueous Primer

DESCRIPTION

AP-1662 is a low gloss aqueous primer for PVC, foam and other polyolefin substrates.

APPLICATIONS

The aqueous primer is designed to be applied via gravure roll or sprayed onto the substrate to improve adhesion and blocking.

FEATURES

- Low Gloss
- Good PVC Adhesion
- Flexible
- Good Blocking resistance

PROPERTIES

Percent Solids, weight	20 – 24%
Gloss	≤1.0
pH, typical value	7 - 10
Viscosity, cps	100 - 350

STORAGE

Store in a cool, dry place, preferably less than 80°F to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.