A Step Ahead…

QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

Technical Data Sheet- Leather Finishing Products

Product Code: JK-691FD

DESCRIPTION

JK-691FD is a very hard, NMP free, high performance aliphatic polyester polyurethane dispersion.

APPLICATIONS

- Additive for leather topcoat applications to enhance abrasion and stain resistance.

FEATURES

- Excellent water resistance
- Good chemical resistance
- Tough film properties
- Internal Cross Linking

PROPERTIES

Percent Solids, weight	33
Percent Solvent, weight	8.0
Specific Gravity, 25°C	1.04
pH, typical value	8.6
Viscosity, cPs	73

FILM PROPERTIES

Tensile Strength	7500psi
Elongation	400%
Modulus	5200psi

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.