QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead…

Technical Data Sheet- Leather Finishing Products

Product Code: PR-1245

DESCRIPTION

PR-1245 is a medium hard, NMP free, high performance aliphatic polyether polyurethane dispersion.

APPLICATIONS

- Topcoat and intermediate coats for leather applications where exceptional hydrolytic stability, flexibility, and abrasion resistance is required.

FEATURES

- Exceptional hydrolysis resistance
- Excellent Bally Flex properties
- Excellent cold flex properties
- Tough film properties with unique hand feel

PROPERTIES

Percent Solids, weight	34
Specific Gravity, 25°C	1.04
pH, typical value	8.4
Viscosity, cPs	120

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.