QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead…

Technical Data Sheet- Leather Finishing Products

Product Code: PR-1500

DESCRIPTION

PR-1500 is a medium hard, NMP free, high performance aliphatic polyester polyurethane dispersion.

APPLICATIONS

- Topcoat and intermediate coat leather applications where excellent abrasion resistance, surface flow, and flexibility are required.

FEATURES

- Excellent abrasion resistance
- Excellent water resistance
- Tough flexible low tack film

PROPERTIES

Percent Solids, weight	35
Specific Gravity, 25°C	1.04
pH, typical value	8.2
Viscosity, cPs	180

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.