QUAKER COLOR
DIVISION OF McADOO & ALLEN, INC.
201 S. HELLERTOWN AVENUE P.O. BOX 219
QUAKERTOWN, PENNSYLVANIA 18951-0219
(215) 536-3520 FAX (215) 536-6464
www.quakercolor.com

A Step Ahead…

**Technical Data Sheet- Leather Finishing Products**

Product Code: XL-1219 Crosslinker

## DESCRIPTION

A multifunctional, water based, polycarbodiimide crosslinker used to enhance the physical properties of leather coatings.

## APPLICATIONS

Should be used at levels between 0.5-3% to enhance the physical properties of most leather coatings. Physical properties like blocking resistance, water resistance, and long term durability will all be improved with the incorporation of XL-1219 Crosslinker.

## FEATURES

- Low viscosity
- Water based
- High functionality
- Excellent pot life

## PROPERTIES

| | |
|---|---|
| Percent Solids, weight | 40% |
| Specific Gravity, 25°C | 1.04 g/cm3 |
| pH, typical value | 11.4 |
| Viscosity, cPs | 90 |

## STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of twelve months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.